

# EP7 Hardware / Software I&T Configuration

## Part of the EPx Production Cell

Source: [EDF \(PDPS\)](#)

Source: [HP loaner](#)

Source: [MSFC](#)

Source: [BUY \(in\)](#)

Source: [epdatasrv](#)

HP9  
sparrow  
HP 735  
256MB, 4G

HP10  
ephp  
HP J210  
256MB, 4G

SGI4  
epsgqi  
Challenge  
256MB, 4G

SUN8  
epsun  
sun 20/71  
256M, 4G

SUN  
epdatasrv  
sparc 20  
128M, 2G

JX 9.0.5  
DCE 1.5.1 (auto)  
E 1.03  
E Servers (CDS,DFS,Sec) 1.03  
if  
base OpenClient (sybase 10)  
base OpenClient (sybase 11)  
MP Agent (local)  
scape Navigator 2.0x  
sic 2.7  
S Application Server)  
S Client)

HPUX 9.0.7  
OODCE 1.5.1  
DCE 1.03  
Motif  
Sybase Server (sybase 11)  
Sybase OpenClient (sybase 11)  
HP OpenView 4.0  
C++ compiler 3.50  
C compiler 9.77  
Remedy 2.02  
SNMP Agent (local)  
Netscape Enterprise Server 2.0 (httpd)  
(ECS Application Server)

SGI IRIX 5.3  
OODCE for IRIX 5.x  
DCE 1.02  
Motif  
Sybase Server (sybase 10)  
Sybase Server (sybase 11)  
Sybase OpenClient (sybase 10)  
C++ compiler (KAI)  
C compiler 3.19  
C compiler 3.0.1  
SQS  
Netscape Navigator 2.0x  
Mosaic 2.7  
(ECS Client)

Solaris 2.4  
OODCE 1.5.1  
DCE 1.03  
CDE 1.0 + Motif 1.2.4  
Sybase OpenClient (sybase 10)  
C++ compiler 3.0.1/4.0.1  
C compiler 3.0.1  
Netscape Enterprise Server 2.0 (httpd)  
Perl 5.0  
Illustra 3.2  
(DDSRV)  
(SDSRV)

Solaris 2.4  
OODCE 1.5.1  
DCE 1.03  
CDE 1.0 + Motif 1.2.4  
Sybase OpenClient (sybase 10)  
Netscape Navigator  
Mosaic 2.7  
(ECS Client)

tes:

- 1) All machines should be configured as:  
Clearcase Clients
- 2) Testers (8) must be able to access the following machines on the EDF infrastructure:
  - XRunner/LoadRunner (sim)
  - DDTs (triton)
- 3) The UNIX userid, ep7itadm, should be created to login to any of these machines
- 4) The DCE account name, ep7itadm, should be created to login to this cell